

3T Borehole



The 3T Borehole (3TB) offers reliable, high quality performance in long period monitoring applications.

KEY FEATURES

Covers the complete seismic spectrum with a single transfer function

120 s to 50 Hz or 360 s to 50 Hz, other bespoke options available on request

Hybrid velocity-acceleration responses available offering unrivalled dynamic range.

Single-jaw hole lock for inner borehole diameters of 99 to 203 mm, or backfill with sand to minimise convection

Waterproof and durable with O-ring seals throughout

Built-in inclinometer option for attitude checking at depth

Operates with a tilt tolerance of up to 2.5 ° with an option to increase this to 12.5 °

Strain relief mechanism fully isolates the sensors from any motions in the load-bearing cable

APPLICATIONS

- > National observatories
- > Microseismic monitoring
- > Robust velocity subsurface modelling
- > Teleseismic earthquake monitoring
- > Nuclear test ban treaty monitoring



3TB WITH SINGLE JAW HOLE-LOCK

SPECIFICATIONS

SYSTEM	
Configuration / Topology	Triaxial orthogonal (ZNE)
PERFORMANCE	
Velocity output band	3T-120: 120s (0.0083 Hz) to 50 Hz 3T-360: 360 s (0.0028 Hz) to 50 Hz Contact Güralp to discuss other frequency response options
Output sensitivity	1500 V/ms ⁻¹ (2 x 750 V/ms ⁻¹) differential standard output (full-scale clip level of 13 mm/s) Contact Güralp to discuss alternative high sensitivity (high gain) options
Peak / Full scale output	Differential: ±20 V (40 V peak-to-peak) Single-ended (e.g. mass positions): ±10 V (20 V peak-to-peak)
Sensor Dynamic Range	167 dB at 1 Hz (Full octave width across 1 Hz)
Self-noise	3T-120: Below NLNM 166 s (0.006 Hz) to 10 Hz 3T-360: Below NLNM 200 s (0.005 Hz) to 10 Hz
Cross axis rejection	65 dB
Linearity	> 111 dB
Lowest spurious resonance	> 140 Hz
Transfer function	User manual is available to download from the website. Each sensor is provided with full calibration details including measured sensitivity, measured frequency response and instrument poles and zeros
Calibration controls	Independent signal & enable lines exposed on sensor connector
Operational tilt	Up to 2.5 ° (option to increase this to 12.5 °)

MASS / MONITORING CONTROL	
Locking	Remote auto mass lock/unlock
Mass centre	Remote automatic mass centreing
POWER	
Power voltage range	11– 30 V DC* (24 V DC recommended)
Power consumption (at 12 V DC)	3 W
*Power voltage for operation of this unit only. Connection to additional instrumentation or use of longer cables may result in a higher input voltage requirement.	
ENVIRONMENTAL	
Operating temperature	-20 to +75 °C
PHYSICAL	
Instrument diameter	89 mm
Inner borehole diameter	99 mm to 203 mm
Case height (exc. lifting bail)	795 mm without hole-lock 1280 mm with single jaw hole-lock
Enclosure/Materials	Stainless steel casing Gold plated contacts O-ring seals throughout
Communication / Connectors	100 bar/10 MPa waterproof connector
Hole-lock install mechanism	Spring-loaded single jaw with passive skids or studs (>60 kg force)
For deployments exceeding 100 metres in depth, we recommend the integrated Downhole Minimus digitiser. For more information see the Borehole brochure or datasheet DAS-MIN-0003	

Güralp Systems Limited
Midas House
Calleva Park
Aldermaston
Reading
RG7 8EA
United Kingdom

T +44 118 981 9056
F +44 118 981 9943
E sales@guralp.com

www.guralp.com

In the interests of continual improvement with respect to design, reliability, function or otherwise, all product specifications and data are subject to change without prior notice.

DAS-BHO-0001 Issue R