

MINIMUS MINIMUS+

SMART SEISMIC DIGITISER WITH ADVANCED DATA-PROCESSING CAPABILITY AND SOFTWARE COMMUNICATIONS



Compact and low-power smart seismic digitiser with the option of four or eight primary digitisation channels.

KEY FEATURES

- > Advanced software communications for quick and easy instrument and data management
- > Hot-swappable and dual-redundant microSD storage
- > Select from GNSS or PTP timing sources
- > Access real-time data manipulation tools such as Quick Seismic Characteristic Data protocol and Maximum, Minimum and Average calculations

FOR EARLY WARNING APPLICATIONS:

- > Ultra low-latency capability
- > Multi-instrument voting for mitigating false-positive alerts
- > Reduce telemetry load by streaming only derived values at trigger
- > Common Alert Protocol (CAP) enabled for automated emergency warning

Minimus


The Güralp Minimus (four channel) and Minimus+ (eight channel) are advanced 'smart' seismic digitisers, packed with a host of features that make them the ideal plug and play solution for rapid deployments and multi-scale networked arrays.

ENCASED IN AN ENVIRONMENTALLY SEALED, HARD ANODISED ALUMINIUM CASING TO WITHSTAND THE HARSHTEST OF ENVIRONMENTS, THE MINIMUS AND MINIMUS+ HAVE AN INTERNAL THERMOMETER AND A HUMIDITY SENSOR TO ALERT YOU TO ANY MOISTURE INGRESS.

MINIMUS DIMENSIONS:



MINIMUS+ DIMENSIONS:



Multidisciplinary functionality with simple instrument and data management.

The four channel Minimus can simultaneously accommodate a triaxial analogue sensor, an auxillary input e.g. for infrasound; a Radian posthole; plus its own internal MEMS accelerometer (2g).

The eight channel Minimus+ accommodates all of the above plus an additional triaxial analogue seismic sensor and auxillary input.

Integrated network connectivity enables the Minimus to be controlled remotely using Güralp Discovery, our software platform, or via a standard web browser. Discovery allows the user to identify the instrument IP address via a Cloud registry server or data centre, eliminating the need for static IP addresses.

Discovery also provides simple instrument and data management with access to hardware State-of-Health (SoH); data streaming; GNSS location; instrument response and calibration values.

For added confidence during deployments, the GüVü Bluetooth app, displays waveforms, orientation, temperature and humidity data, for instant checking of installation integrity.

Key features

24-bit, four channel (Minimus) or eight channel (Minimus+) digitiser

Compatible with any analogue seismic sensor

Ultra-low-latency mode for Earthquake Early Warning - when used with GDI protocol, transmission can be achieved in 40 ms

Industry standard triggering algorithms for EEW (STA/LTA and Threshold)

Multi-instrument voting for mitigating false positive alerts

Powerful real-time data Transforms: mathematical operations applied to real-time and recorded data e.g. integration; differentiation; high and low-pass filters

Quick Seismic Characteristic Data (QSCD) protocol and Maximum, Minimum and Average (MMA) calculated on selected time window.

Seismic event table displaying events detected using trigger algorithms with links to download event data (pre and post event time is user-configurable)

Common Alert Protocol (CAP) enabled for automated emergency warning

Identification of IP address via Discovery and Cloud registry server

Remote instrument and data management via easy-to-use Discovery software

Scream!™ compatible

GüVü Bluetooth app for installation integrity checking (Android)

Versatile streaming and filtering options.

Users can select sample rates of up to 5000 samples per second with the option to simultaneously stream multiple sample rates in addition to two recording rates.

Data are locally recorded in miniSEED (with metadata stored in dataless SEED format) and can be streamed in realtime using GCF (Scream!), GDI-link and SEEDlink.

Access real-time data manipulation tools such as Quick Seismic Characteristic Data (QSCD); Maximum, Minimum and Average (MMA) calculations and transforms such as integration, differentiation and low and high pass filters.

For Earthquake Early Warning applications, the Minimus has an ultra-low-latency mode running causal filters alongside traditional acausal filters. When used with our GDI protocol, this low-latency mode means network transmission can be achieved in 40 milliseconds (sample rate and network dependent). Other EEW features include industry standard triggering algorithms for EEW (STA/LTA and Threshold); multi-instrument voting for mitigating false positive alerts; and Common Alert Protocol (CAP) for automated emergency warning.

Dual redundant 16 GB microSD cards (1 fixed, 1 hot-swappable) with options of 32 GB, 64 GB or 128 GB

Select from GNSS (GPS and GLONASS, BeiDou optional) or PTP (Precision Time Protocol) timing sources

Minimus+ supports Power Over Ethernet (POE) which significantly reduces complexity when installing local arrays

Applications

- > Earthquake Early Warning Systems
 - > Volcanology
 - > Multi-scale seismic networks
 - > Structural health monitoring
 - > Hydrocarbon exploration
 - > Permanent reservoir monitoring
 - > Induced seismicity detection
 - > Explosion monitoring
-

Minimus: Güralp Discovery Software*

*See Discovery datasheet for more details

Discovery dramatically simplifies instrument and data management and gives users powerful tools via a web interface:

- > Identify instrument IP address
- > Analysis of hardware State of Health
- > Data streaming control
- > Remotely upgrade digitiser firmware
- > Upload configuration to multiple units simultaneously
- > Advanced analysis on waveform data such as PSD and spectrogram

Güralp Systems - Discovery

File Edit View Help

	Status	Label	System	Name	Serial#	Firmware Ver	WAN Address	LAN Address	Uptime	Last Contact	Latit
24		DEMO 83	Minimus	MIN-C456	50262	1.1-1022	89.213.16.113	10.10.0.36	1 days 18 Hrs	Just Now	0.00C
25		NO LABEL	Minimus	MIN-D956	55638	1.1-1022	89.213.16.113	10.30.0.81	16:57:58	Just Now	0.00C
26		NO LABEL	Minimus	MIN-1F58	8024	1.1-1022	89.213.16.113	10.20.0.168	23:40:08	Just Now	51.3C
27		NO LABEL	Minimus	MIN-2B57	11095	1.1-1022	89.213.16.113	10.30.0.87	6 days 17 Hrs	Just Now	0.00C
28		NO LABEL	Minimus	MIN-2A58	10840	1.1-1022	89.213.16.113	10.20.0.50	17:48:29	Just Now	51.3C
29		NO LABEL	Minimus	MIN-2B58	11096	1.1-1022	89.213.16.113	10.20.0.64	17:34:48	Just Now	51.3C
30		NO LABEL	Minimus	MIN-2C58	11352	1.1-1022	89.213.16.113	10.20.0.67	17:36:48	Just Now	51.3C
31		NO LABEL	Minimus	MIN-2D58	11608	1.1-1022	89.213.16.113	10.20.0.67	17:36:48	Just Now	51.3C

— NETWORK OVERVIEW

DIGITISER WEB INTERFACE —

Status Network **Setup** Power Trigger Data Flow Data Record

System type: Minimus | Host label: NO LABEL | Host name: MIN-C555 (10.10.0.13) | Serial number: 50517

Digitiser Config Please reboot

Date: Mon 04 Dec 2017 Time: 3:02:49 PM Auto Refresh

Label: NO LABEL Station Name: TEST Network Code

Bluetooth PIN: 0000 Filter quality: High

Deploy mode: Normal Deploy

Applied Rotation

Analogue 0: 0° Radian 2: 0° Radian 3: 0° Radian 5: 0° Radian 6: 0° Radian 7: 0°

Reboot

Analogue Sensor

Input Gain: Unity Sensor Type: Fortis

Status Network Setup Power Trigger Data Flow Data Record Storage Logout Help

System type: Minimus | Host label: Support | Host name: MIN-C555 (10.10.0.13) | Serial number: 50517

System Status

General information

Host name	MIN-C555	Host label	Support	System type	Minimus	Product type	Minimus
Serial number	c555	Firmware version	1.1-1022	IP-v4 address	10.10.0.13 (DHCP)	10/10 network and status	10/10
Digitiser temperature	38.1 °C	Digitiser humidity	25%	Input voltage	12.75 V	Power over Ethernet voltage	3.75 V

GNSS status

GNSS connection status: Connected Last timestamp: 2017-11-29 15:22:38

Last lock time: 2017-11-29 07:00:48 GNSS stability: GOOD

Latitude: 51.3607 Longitude: -1.9311

Altitude: 121.50 m Horizontal dilation of precision: 6.78

GNSS PPS status: Tracked PPSing GNSS NMEA stream: Input OK

GNSS Lock state: 2D locked 3D locked Number of satellites: 12 In view: 13

MicroSD status: Recording MicroSD total: 66817.408 KiB MicroSD used: 5726540 KiB MicroSD free: YES



Number of sensors detected: 1

Sensors

Serial number (ID)	c555	Firmware ver (ID)	3.11
Serial number (Z ID)	22759	Sensor number (ID)	-4958
		Sensor number (C ID)	-10945

— DIGITISER CONFIGURATION

REAL-TIME VIEWER —




— INSTRUMENT POWER SPECTRAL DENSITY (PSD) GRAPHS

Minimus: GüVü Bluetooth App

Check the integrity of your installation instantaneously

GüVü displays a range of instrument data such as waveforms, orientation, temperature and humidity data. Additionally you can lock/unlock and centre the masses of analogue sensors, reboot Minimus and alter sample rates without instrument disturbance. GüVü can also format replacement SD cards. A deployment status report can then be emailed for a detailed record of the installation.



UNIQUE INSTRUMENT SERIAL NUMBER
MEDIA ACCESS CONTROL (MAC) ADDRESS

INSTRUMENT TEMPERATURE
INSTRUMENT INTERNAL HUMIDITY
POWER SUPPLY
MICROSD CARD STATUS

DATA RECORDING STATUS
GNSS RECEIVER LOCATION

GNSS TIME-LOCK STATUS

SENSOR MASS POSITIONS

MAIN SENSOR OUTPUTS

INSTRUMENT ORIENTATION (RADIAN/FORTIMUS)

Minimus Minimus+



SPECIFICATIONS

SENSOR INPUTS	
Primary digitisation channels	Minimus: four at 24 bits Minimus+: eight at 24 bits Differential input: 40 V peak-to-peak (± 20 V). Also compatible with single-ended inputs: 20 V peak-to-peak (± 10 V)
Secondary channels	Minimus: three analogue channels for sensor mass positions, one internal calibration channel at 16 bits Minimus+: six analogue channels for sensor mass positions, two internal calibration channels at 16 bits
Internal environmental channels	Humidity Temperature Supply voltage MEMS accelerometer (three component) Magnetometer (three component)
Input impedance	50 k Ω
PERFORMANCE	
ADC converter type	Delta-sigma
ADC conversion delay	6 μ s
Output format	32-bit
Dynamic Range	>142 dB at 100 samples per second
Gain drift	3 ppm / °C
Common-mode rejection	>110 dB
DATA PROCESSING	
Output rates available	1 sample per hour up to 5000 samples per second for primary channels, user-selectable Multiple independent data streams at different sample rates for all channels (transmission and recording) Up to 500 samples per second for environmental channels
Decimation filters	± 2 , ± 3 , ± 4 , ± 5 decimation (Causal / Acausal)
Out-of-band rejection	>194 dB
Data transmission mode	Continuous and trigger modes
Triggered data	Retrievable using event table in digitiser's web page. User selectable pre and post event time.
Trigger modes	STA/LTA, Threshold
Output streams	Direct output of PGA, PGV and PGD without external software
Selectable gain	Unity, $\times 2$, $\times 4$, $\times 8$, $\times 12$, $\times 64$
TIMING AND CALIBRATION	
Timing source precision	Accuracy when GNSS locked ± 50 ns. Typical drift when unsynchronised (without GNSS) <1 ms per day
Timing sources	GNSS (GPS and GLONASS, BeiDou optional), PTP (Precision Time Protocol)
Calibration signal generator	Triangle, Step, Sinewave or Broadband noise with adjustable amplitude.

OPERATION AND POWER USAGE	
Operating temperature	-20 to +60 °C
Relative humidity range	zero to 100 %
Power supply	10 - 36 V DC* Optional 9 V DC available
Power consumption at 12 V DC (Minimus)	< 1 W in power save mode with no GNSS or Ethernet < 1.65 W in standard mode with GNSS and 10 Mb/s Ethernet output
Power consumption at 12 V DC (Minimus+)	< 1.1 W in power save mode with no GNSS or Ethernet < 1.75 W in standard mode with GNSS and 10 Mb/s Ethernet output
<i>*Power voltage for operation of this unit only. Connection to additional instrumentation or use of longer cables may result in a higher input voltage requirement.</i>	
SOFTWARE	
Operating system	Windows and Linux compatible
Communication technologies supported Minimus and Minimus+:	Ethernet (10/100BASE-T)
Minimus+ only:	Power over Ethernet (PoE)
USER INTERFACE	
Configuration and control	(Ethernet) Güralp Discovery - free download, web browser interface. GüVü Bluetooth app (Android)
DATA COMMUNICATION	
Data recording formats	miniSEED (metadata stored in dataless SEED format)
Data streaming protocols (via Ethernet)	GCF (Scream!), GDI-link ¹ and SEEDlink ¹ ('metadata sent in RESP, StationXML and dataless SEED file formats)
Memory and storage	Dual redundant 16 GB microSD cards (1 fixed, 1 hot-swappable) Option for 64 GB or 128 GB
RAM	256 MB
PHYSICAL CHARACTERISTICS	
Casing type	Environmentally sealed, hard anodised aluminium
Environmental sensor	Humidity and temperature
Weight	Minimus: 674 g (disconnected) Minimus+: 782 g (disconnected)
Dimensions	Minimus: 134 mm \times 99 mm \times 45 mm Minimus+: 134 mm \times 139 mm \times 45 mm
Connector type	MIL-DTL-26482 Series 1: Analogue - 26 way (Minimus $\times 1$; Minimus+ $\times 2$) Ethernet - 8P8C (RJ45) Power - 4 pin Digital - 10 pin LEMO : GNSS/serial - 14 pin
Global navigation satellite system (GNSS)	Compact, encapsulated, waterproof, precision timing GPS/GLONASS (BeiDou optional) receiver
Environmental protection	IP68 - protection against effects of prolonged immersion at 3 m depth for 72 hours

Güralp Systems Limited
Midas House
Calleva Park
Aldermaston
Reading
RG7 8EA
United Kingdom

T +44 118 981 9056
F +44 118 981 9943
E sales@guralp.com

www.guralp.com

In the interests of continual improvement with respect to design, reliability, function or otherwise, all product specifications and data are subject to change without prior notice.

CE
DAS-MIN-0001 Issue S